



RTD ELEMENT POTTED IN
300 SERIES STAINLESS
STEEL PROBE HOUSING

1/2"-14 NPT
THREAD (RHT)

BLACK WIRE

RED WIRE

WHITE WIRE

RTD

REV	DESCRIPTION	DATE	APP
0	INITIAL RELEASE	02/11/2019	DD
REVISION HISTORY			

EI SENSOR TECHNOLOGIES

www.ei-sensor.com

© COPYRIGHT

P/N ERP10010

RTD PROBE ASSEMBLY

DRAWN BY: DAN DANKERT

SCALE: NONE LAYER: 0 OF 2

REV: 0 DATE: 02/11/2019

RTD ELEMENT RESISTANCE @ 0°C = 100 Ω ± 0.06%

RTD ELEMENT ACCURACY @ 0°C = ± 0.15°C

RTD ELEMENT ACCURACY = DIN 43760 CLASS "A"

TCR = 3,850 ppm/°C

MAXIMUM TEMPERATURE RATING = +105°C

MOISTURE RESISTANT PROBE ASSEMBLY

ROHS COMPLIANT

This PROPRIETARY document is the property of EI Sensor Technologies. It is confidential in nature, non-transferrable and issued with the understanding that it is not to be traced or copied without permission, and is returnable on demand.