



PART NUMBER	PACKAGING
ERTS1202A101A-B	BULK
ERTS1202A101A-D	TAPE & REEL (SENSOR SIDE DOWN)
ERTS1202A101A-U	TAPE & REEL (SENSOR SIDE UP)

REV	DESCRIPTION	DATE	APP
0	INITIAL RELEASE	02/18/2020	DD

REVISION HISTORY

EI SENSOR TECHNOLOGIES www.ei-sensor.com © COPYRIGHT	RTD ELEMENT	
	DRAWN BY: DAN DANKERT	
P/N ERTS1202A101A-	SCALE: NONE	LAYER: 0 OF 2
	REV: 0	DATE: 02/18/2020

This PROPRIETARY document is the property of EI Sensor Technologies. It is confidential in nature, non-transferrable and issued with the understanding that it is not to be traced or copied without permission, and is returnable on demand.

RESISTANCE @ 0°C = 100 Ω ± 0.06%
 ACCURACY @ 0°C = ± 0.15°C
 ACCURACY CLASS = IEC 60751 F 0.15
 TCR = 3,850 ppm/°C
 DISSIPATION CONSTANT = 7 mW/°C NOMINAL (AIR)
 MAXIMUM APPLIED CURRENT = 1 mA
 THERMAL TIME CONSTANT = 4.2 SECONDS NOMINAL (AIR @ 1m/SECOND)
 TEMPERATURE RATING = -50 TO +150°C

ROHS COMPLIANT

PACKAGING: SEE TABLE